

Dishwasher **ESL5205LO**





Opens the door to dry dishes Our AirDry technology finishes each dishwashing cycle with a breath of fresh air. The door is set slightly ajar during the last part of the drying phase without you having to lift a finger. Natural air can circulate inside the machine, leaving your plates and cutlery completely dry.

Product Benefits & Features

Efficient clean for even the dirtiest loads The intensiv program ensures an efficient and powerful clean for even the dirtiest loads, thanks to a 70°C water jet.	 Energy efficiency (2010/30/EC): A+ Installation: FI Loading capacity: 13 IEC settings Noise level: only 49 (dB(A) re 1 pW) (2010/30/EC) Water and energy consumption: 11 I, 1.039 kWh for program Eco 50 5 programmes, 4 temperatures Dishwasher programmes: Eco 50°, Intensive 70°, Normal 65°, QuickPlus 60°, Rinse & Hold Panel with symbols Thermo Efficient System Warm water connection up to 60°C Delay start option: 3h SENSORCONTROL dishwasher Indications for salt and rinse aid Height adjustable upper basket Upper basket with Foldable cup shelves Lower basket with Fixed plate racks Cutlery basket Waterstop System Built-in H(min/max)xWxD (mm): 820/880 x 600 x 550
Fast and efficient performance For when you have a light load, the 30-minute quick wash programme of the dishwasher offers a timesaving solution with perfect washing results.	



Get a little more freedom - delay the start of the dishwasher by 3 hours

Thanks to the Delay Start function, you can program this dishwasher to start the next cycle in up to three hours.



Dishwasher **ESL5205LO**

Product Specification

Product Installation	Built_In
Product Typology	Full_Width(60cm)
Product Classification	Performance
Installation	FI
Cabinet type of	60 FI SLIDING
Panel colour	Grey
Door colour	None
Side walls colour	Rough zinc coated
Type of timer min.	EDW503
Push button functions	Delay start, On/off, Program selection
Knob/Command functionality	No
Programmes number of	5
Number of temperatures	4
Dishwasher programs	Eco 50°, Intensive 70°, Normal 65°, QuickPlus 60°, Rinse & Hold
Indicator programme	LED
Indicators display	None
Indicators other	Buzzer, Delay start 3h, End, Rinse aid, Salt
Height total	818
Width mm	596
Depth mm	550
Tub material	Stainless steel
Heating element type of	Interheater

Inlet hose type of	Aqua control
Inlet hose length	150
Water supply	Cold or hot
Anti-flood device	Floating switch
Drying system	AirDry Technology
Softening regulation	10 steps
Top spraying level	None
Lower spray arm	Standard

