

BS-1015BSB

COMPACT SPEAKER

The BS-1015BSB is the voice alarm certification product. 2 way speaker system is suitable for announcement and music use in wide frequency range. Speaker design that harmonize with the venue's architecture and decor.



Order no: BS-1015BSB
 Alternative products: VX-3008F, VX-3004F,
 VX-3016F, SX-2000SM, VX-2000,
 SX-2100AO, SX-2100AI, VM-3360VA,
 VM-3240VA, VM-3240E, VM-3360E, VP-3504,
 VP-3154, VP-3304, VP-2421incl, VP-2421,
 VP-2241, VP-2241incl, VP-2122incl, VP-2122,
 VP-2064, VP-2064incl


Specifications

Frequency response	80 Hz - 20 kHz
Connection	Ceramic screw terminals, thermal fuse
Sensitivity (1#V, 1#m) (combined)	90 dB
Speaker component	Low: 5" cone-type High balanced dome tweeter
Directivity angle horizontal	220 °
Directivity angle vertical	330 °
Rated input	15 W, 7,5 W
Tappings	15 / 10 / 5 W (100 V), 7.5 / 5 / 2.5 W (70 V)
Rated impedance	70 V, 100 V
Dimensions (W x H x D)	196 x 290 x 186 mm
Dimensions (ø x D)	x 186 mm
Finish	ABS resin, paint, black (RAL 9011 or equivalent)
Operating temperature	-10°C to +50°C

BS-1015BSB

COMPACT SPEAKER

Appearance



Top View

