ESF5542LOW





A tailored treatment, everything accommodated

By completely tailoring the compartments inside our dishwasher, everything can fit in at once. The unique foldable racks and liftable basket mean you can reconfigure inside the machine to suit all shapes and sizes.

Product Benefits & Features



Clean dishes always ready when you need them Need clean dishes in a hurry? That's no problem thanks to the Time Manager feature on this dishwasher, which makes it possible to reduce the cycle time by half.

Run vour dishwasher whenever it suits vou

This dishwasher gets to work when you want it to. With

its Delay Start function, you can load it when you want

to and program it to start at the time that suits your

schedule. You can delay the start by up to 24 hours.

- Energy efficiency (2010/30/EC): A++
- Installation: FS
- Loading capacity: 13 IEC settings
 Noise level: only 44 (dB(A) re 1 pW) (2010/30/EC)
- Water and energy consumption: 9.9 l, 0.92 kWh for program Eco 50
- Glass protection program
- 6 programmes, 4 temperatures
- Dishwasher programmes: AutoFlex 45°-70°, Eco 50°, GlassCare 45°, Intensive 70°, QuickPlus 60°, Rinse & Hold
- Text/symbol panel
- Panel with symbols
- Auto Off function
- Thermo Efficient System
- Warm water connection up to 60°C
- Delay start option from 1 to 24 hours
- · Remaining time indication
- SENSORCONTROL dishwasher
- Water sensor detects the level of dirt and adjusts water consumption
- · Indications for salt and rinse aid
- Upper basket with FlexiLift
- · Height adjustable upper basket, even when fully loaded
- Upper basket with 2 Soft Spikes, Foldable cup shelves, Plastic handle
- Lower basket with 2 foldable plate racks, Plastic handle
- Cutlery basket
- Waterstop System



Spotless and sparkling, in every cycle

Our AutoFlex programme with smart sensor adjusts the consumption of each dishwashing cycle to the size and cleanliness of every load. Using only what is needed so that all dishes emerge spotless. No wasted water, energy or time. Just efficiently sparkling, every time.





ESF5542LOW

Product Specification		
Product Installation	Free_Standing	Depth mm
Product Typology	Full_Width	Tub material
Product Classification	Performance	Heating element type
Installation	FS	Inlet hose type of
Cabinet type of	60 FS soft	Inlet hose length
Panel colour	White	Water supply
Door colour	White	Anti-flood device
Side walls colour	White	Drying system
Type of timer min.	EDW 1600	Softening regulation
Push button functions	Delay start, On/off, Option, Program selection, Start	Top spraying level Lower spray arm
Knob/Command functionality	No	Lower spray ann
Programmes number of	6	
Number of temperatures	4	
Dishwasher programs	AutoFlex 45°-70°, Eco 50°, GlassCare 45°, Intensive 70°, QuickPlus 60°, Rinse & Hold	
Indicator programme	LED	
Indicators display	Delay start, Remaining time, Service code	
Indicators other	Delay start 1h-24h, Drying phase, Program selected, Rinse aid, Salt, TimeManager, Washing phase, XtraDry	
Height total	850	
Width mm	600	

Depth mm	625	
Tub material	Stainless steel	
Heating element type of	Interheater	
Inlet hose type of	Aqua control	
Inlet hose length	150	
Water supply	Cold or hot	
Anti-flood device	Floating switch	
Drying system	AirDry Technology	
Softening regulation	10 steps	
Top spraying level	None	
Lower spray arm	Standard	